

MULTI-CONDUCTOR CABLES INSULATED IN FEP + FEP T200°C cURus+ ROUND SHEATH IN SILICONE

XH---

2008

RA[®]
cURus

Type of insulation:

FEP + FEP UR STYLE 21167
+ external sheath in round SILICONE

Working temperature:

T 200°C
T 180°C for the silicone

Type of conductor:

NICKEL-PLATED COPPER

Working voltage:

600 V

Inner cable in conformity to the standard:

UL 758 AWM STYLE 21167

Approval marks:

cURus(for the inner cable in FEP+FEP)



PROCESSED WIRE **RA** FILE E221012

RESPOOLED WIRE **RA** FILE E221012

• AWG table of the cores:

Code	AWG	Conductor strand	Cores colours*	Cores position	Shape	Dimension ±0,2 mm
XH28-	2 x 18	48 x 0,161	tn tb	P	round	ø 6,0
XH38-	3 x 18	48 x 0,161	tn tb + ground	P	round	ø 6,0

• Other AWG on request.

* Table of the lines colours to identify the cores:

tn = black tb = white

* Cores position table:





P = parallel

XF--T: version with insulated 24 AWG steel self-supporting wire rope, with 35 kg breaking load.

• AWG and multiple table of the cores for the version with steel wire rope:

Code	AWG	Conductor strand	Cores colours*	Cores position	Shape	Dimension ±0,2 mm
XF28-	2 x 18	48 x 0,161	tn tb	P	round	ø 6,1
XF38-	3 x 18	48 x 0,161	tn tb + ground	P	round	ø 6,4

• UR approval printing of the inner cable, on the sheath, with white ink.



• Table of available colours:

T = transparent (sheath and cores)

N = black

B = white

- Other colours on request.

